

2010 ESCAPE/ESCAPE HYBRID /// TRAILER TOWING

Escape Towing Selector

- This chart can be used to locate the vehicle's GCWR and trailer weight with a variety of engine/axle ratio combinations.
- The GCWR column shows the maximum allowable combined weight of vehicle, trailer, hitch and cargo (including passengers).

- Maximum loaded trailer weight assumes a towing vehicle with mandatory options, no cargo, and a driver (68 kg/150 lb.) only. The weight of additional options, passengers and cargo must be deducted from this weight.
- Consult an up-to-date Order Guide for Trailer Towing Package option details and contents.

ESCAPE/ESCAPE HYBRID					
Engine	Transmission	Axle Ratio	Maximum GCWR <i>kg (lb.)</i>		Maximum Loaded Trailer Weight <i>kg (lb.)</i>
			FWD	4WD	
ESCAPE					
2.5L Duratec 25 I4	Manual	4.13	2268 (5000)	-	680 (1500)
2.5L Duratec 25 I4	Automatic	3.51	2295 (5060)	2358 (5200)	680 (1500)
3.0L Duratec 30 V6	Automatic	3.51	3238 (7140)	3311 (7300)	1587 (3500) ¹
ESCAPE HYBRID					
2.5L Atkinson Cycle Duratec I4/ Permanent Magnet AC Synchronous Motor	eCVT	3.04 Final Drive Ratio	2204 (4860)	2277 (5020)	454 (1000) ²

¹ Requires Class II Trailer Towing Package

² Conventional trailer hitches are not compatible with Escape Hybrid components.

Frontal Area Considerations

- Not to exceed base vehicle frontal area of 2.22 m² (24 sq. ft.):
 - 2.5L Duratec 25
- Not to exceed 2.97 m² (30 sq. ft.):
 - 3.0L Duratec 30 V6

Required Equipment

- 3.0L Duratec 30 V6 for trailers over 680 kg (1500 lb.)

Optional Trailer Towing Equipment

- Class II Trailer Towing Package (XLT V6 and Limited V6)
 - Four-wire harness and four-pin connector
 - Auxiliary automatic transmission oil cooler
 - Hitch receiver
 - Weight-carrying capacity: 1587 kg (3500 lb.)